



型式	1RF-M	2RF-M	2.8RF-M	3RF-M	5RF-M	7.5RF-M	10RF-M	15RF-M	
額定荷重 (Ton)	1	2	2.8	3	5	7.5	10	15	
標準揚程 (M)	6、8、12								
捲上速度 (M/min)	50HZ	7	6.3	5.3	5.3	6	4.2	4.3	4.2
	60HZ	8.4	7.5	6.3	6.3	7.2	5	5.2	5
捲上馬達 (Kw)	1.5	3.75	3.75	3.75	7.5	7.5	11	18.5	
鋼索直徑 (mm)	Φ8	Φ10	Φ12	Φ12	Φ16	Φ14	Φ16	Φ18	
鋼索掛數	2/1					4/2			
控制方式	懸垂式押扣開關								
電源需求	3Φ220/380/415/440/460V 50/60Hz								

型式	1RF-M	2RF-M	2.8RF-M	3RF-M	5RF-M	7.5RF-M	10RF-M	15RF-M		
額定荷重 (Ton)	1	2	2.8	3	5	7.5	10	15		
鋼索掛數	2/1					4/2				
概略尺寸 (mm)	A	6M	490	570	590	670	790	930	1005	*
		8M	560	605	620	700	790	980	1055	1145
		12M	605	675	700	780	870	1080	1250	1275
	B	6M	244	290	420	420	490	625	762	*
		8M	294	330	455	455	490	675	773	870
		12M	355	400	530	530	570	775	913	1000
	Φd	36	40	60		75	85	100	120	
	C	200	200	200	200	270	300	350	380	
	D	Φ26	Φ36	Φ36	Φ36	Φ46	Φ46	Φ51	Φ71	
	E	160	185	215	215	250	250	300	357	
	F	310	330	360	360	410	410	520	635	
	G	140	140	165	165	195	200	200	220	
H	680	830	1030	1030	1260	1120	1250	1600		
淨重 (Kg)	6M	100	154	220	220	415	530	750	*	
	8M	107	162	230	230	420	555	825	980	
	12M	120	176	260	260	465	600	950	1150	